

Cidly Group

Add:2-3/F, Building E, DingFeng Industrial Area, Shiyan, Baoan, Shenzhen, China

Tel: +86-755-23443316

Cell Phone: +86-134-1083-3992

Email:sales6@cidly.com

Website: www.cidly.com

Features

- * Waterproof design , include temperature control .
- * High PAR value with secondary lenses , deep to the bottom of tank .
- * Powered by 3Watt Bridgelux LEDs , high performance , super bright .
- * Pure aluminum with deep fins as the heat sink , best heat conduction .
- * No fans , no noise , best item replace T5 , T8 and HPS
- * Easy connection, just play and plug .
- * UL standard LED driver well protect the LED fixture .
- * Lifetime Hours - 50,000 hours ,environment friendly.

Model No.	Power	Qty of LEDs	Input voltage	Frequency	Length	N.W
WF-48"	62 W	27pcs	100-240VAC	50-60Hz	48"	1.90 Kg
WF-36"	52 W	20pcs	100-240VAC	50-60Hz	36"	2.50 Kg
WF-24"	30 W	13pcs	100-240VAC	50-60Hz	24"	2.90 Kg



Application

- * Offer excellent color rendition to your Plant or Reef Aquarium
- * Promotes high Coral growth